

# 4G wireless technology developments

## Contents

- 1 Overview
  - ◆ 1.1 Definition of 4G
  - ◆ 1.2 4G standards
  - ◆ 1.3 Services where 4G is used
  - ◆ 1.4 4G objectives
- 2 Technology overview
  - ◆ 2.1 Mobile technology roadmap
  - ◆ 2.2 Dashboard Preview
- 3 Like this report?
- 4 WiMAX
  - ◆ 4.1 **WiMAX Dashboard**
  - ◆ 4.2 Standards
  - ◆ 4.3 Companies
  - ◆ 4.4 Products
- 5 WiBro
  - ◆ 5.1 Standards
  - ◆ 5.2 Companies
  - ◆ 5.3 Products Overview
- 6 3GPP Long Term Evolution
  - ◆ 6.1 Standards
  - ◆ 6.2 Companies
  - ◆ 6.3 Products
- 7 HSOPA
  - ◆ 7.1 Standards
  - ◆ 7.2 Companies
  - ◆ 7.3 Products
- 8 3GPP2 Ultra Mobile Broadband
  - ◆ 8.1 Standards
  - ◆ 8.2 Companies
  - ◆ 8.3 Products
- 9 Process Chart
- 10 Like this report?
- 11 Contact Dolcera

## Overview

### Definition of 4G

The 4G will be a fully IP-based integrated system of systems and network of networks achieved after the convergence of wired and wireless networks as well as computer, consumer electronics, communication technology, and several other convergences that will be capable of providing 100 Mbit/s and 1 Gbit/s, respectively, in outdoor and indoor environments with end-to-end QoS and high security, offering any kind of services anytime, anywhere, at affordable cost and one billing.

According to the 4G working groups, the infrastructure and the terminals will have almost all the standards from 2G to 3G implemented. The infrastructure will however only be packet based, all-IP. The system will also serve as an open platform where the new innovations can go with it.

### 4G standards

- WiMAX
- WiBro
- 3GPP Long Term Evolution
- HSOPA
- 3GPP2 Ultra Mobile Broadband

### Services where 4G is used

- Wireless broadband access
- Multimedia Messaging Service
- Video chat
- Mobile TV
- High definition TV content,
- DVB
- Minimal service like voice and data

### 4G objectives

- A spectrally efficient system (in bits/s/Hz and bit/s/Hz/site)
- High network capacity


- A nominal data rate of 100 Mbit/s at high speeds and 1 Gbit/s at stationary conditions as defined by the ITU-R
- A data rate of at least 100 Mbit/s between any two points in the world
- Smooth handoff across heterogeneous network
- Seamless connectivity and global roaming across multiple networks
- High quality of service for next generation multimedia support (real time audio, high speed data, HDTV video content, mobile TV, etc)
- Interoperability with the existing wireless standards
- An all IP, packet switched network

## Technology overview


Mindmap below shows the overview of emerging technologies in 4G


Parameter	4G				
	WiMAX	WiBro	3GPP LTE	HSOPA	3GPP2 UMB
Logo					
Access scheme	OFDMA	OFDMA	SC-FDMA Uplink OFDMA Downlink	SC-FDMA Uplink OFDMA Downlink	OFDMA
Duplex system	TDD/FDD	TDD	TDD/FDD	FDD	FDD
Channel Bandwidth	3.5, 5, 7, 8.75, 10, 15, 20MHz	8.75MHz	1.25, 1.6, 2.5, 5, 10, 15 and 20 MHz	1.25 MHz to 20 MHz	1.25 - 20 MHz
FFT size	128, 256, 512, 1024, 2048	1024	128, 256, 512, 1024, 1536, 2048	128, 256, 512, 1024, 1536, 2049	N/A
Data rate	70 Mbps	30 - 50 Mbps	100 Mbps Downlink 50 Mbps Uplink	14.4 Mbps	275 Mbps Downlink 75 Mbps Uplink
Antenna System	MIMO-AAS smart antenna subsystems. (6 - antenna array)	MIMO-AAS smart antenna subsystems. (6 - antenna array)	MIMO-AAS smart antenna subsystems. (4 - antenna array)	MIMO-AAS smart antenna subsystems.	MIMO-AAS smart antenna subsystems.
FEC scheme	Convolution Code Convolution Turbo Code	Convolution Code Convolution Turbo Code	Convolution Code Turbo Code	N/A	N/A
Modulation	BPSK, QPSK, 16QAM, 64QAM	QPSK, 16QAM, 64QAM	QPSK, 8PSK 16 QAM	16 QAM	BPSK, 8PSK, QPSK, 16QAM, 64QAM
Frequency band	2.3GHz ~ 2.4GHz	2.3GHz ~ 2.4GHz	2010MHz ~ 2025MHz	N/A	450 MHz to 3.6GHz
Cell coverage	10 KM	1 KM	5 - 100 KM	N/A	N/A

## Mobile technology roadmap



Roadmap





Preview of company statistics per protocol



Data Filters

Mobile Wi-MAX (259)

Protocol (93)

QoS (48)

Frame structure (45)

Chipset (19)

Subscriber station (35)

Base station (55)

Router/Gateway (25)

Connectivity (33)

ALL COMPANIES (259)

(Company Tbd) (6)

4G systems (4)

ADAPTIX (7)

ADC (4)

ALCATEL LUCENT (3)

ALTAIR SEMICONDUCTOR LTD (1)

AMIMON LTD. (2)

ARRAYCOMM INC (1)

ATC TECHNOLOGIES LLC (2)

AXESSTEL INC. (1)

All Patent Types

Information

Patent Charts

Patents

Products

Publication	Title
<input checked="" type="checkbox"/> EP1816779A2	Interoperability verification for implementation according
<input checked="" type="checkbox"/> WO2007091245A2	Dual-function wireless data terminal
<input checked="" type="checkbox"/> WO2007095182A2	Adaptive spotbeam broadcasting, systems, methods and
<input checked="" type="checkbox"/> WO2007095860A1	Method and apparatus for wireless resource allocation
<input checked="" type="checkbox"/> US20070201400A1	Opportunistic packet scheduling apparatus and method i
<input checked="" type="checkbox"/> WO2007103026A2	Ofdma resource allocation in multi-hop wireless mesh ne
<input checked="" type="checkbox"/> WO2007106314A2	Mobile station and method for fast roaming with integrity
<input checked="" type="checkbox"/> US20070189235A1	Quality of service based resource determination and allo
<input checked="" type="checkbox"/> US20070189205A1	Method and apparatus for providing and utilizing a non-c
<input checked="" type="checkbox"/> US20070201404A1	Method and system for allocating resources in a commun
<input checked="" type="checkbox"/> US20070189214A1	Apparatus and method for transmitting/receiving signal i

EP1816779A2

Interoperability verification for implementation according to communication standard

Abstract:

An apparatus for verifying interoperability of an implementation of a communication standard includes verifying the implementation against a standard. A communication stream (26), generated by an implementation that is interoperable with the standard, will contain expected pilot information. Using the implementation to be verified, a communication stream (24) is generated, containing pilot information. The generated pilot information is compared (28, 38) with the expected pilot information, and interoperability is determined (44, 46, 48) based on the result of the comparing.

Dolcera Analysis:

null

Claims:

1. An apparatus for verifying interoperability of an implementation of a communication standard includes generating a communication stream (24) containing pilot information; means for comparing the pilot information expected in a communication stream (26) interoperable with the standard, with the pilot information in the communication stream (24) generated by the implementation to be verified, to determine interoperability based on the result of the comparing.  
2. An apparatus for verifying interoperability of an implementation of a communication standard includes generating (26) a communication stream (26) containing pilot information; and comparing the pilot information in the communication stream (26) with the pilot information in the communication stream (24) generated by the implementation to be verified, to determine interoperability based on the result of the comparing.  
3. An apparatus for verifying interoperability of an implementation of a communication standard includes generating a set of pilot information; and comparing the pilot information in the communication stream (26) interoperable with the standard, with the pilot information in the communication stream (24) generated by the implementation to be verified, to determine interoperability based on the result of the comparing.

Preview of patents per protocol

### Data Filters

Mobile Wi-MAX (259)

- Protocol (93)
  - QoS (48)
  - Frame structure (45)
- Chipset (19)
- Subscriber station (35)
- Base station (55)
- Router/Gateway (25)
- Connectivity (33)

ALL COMPANIES (259)

- (Company Tbd) (6)
- 4G systems (4)
- ADAPTIX (7)
- ADC (4)
- ALCATEL LUCENT (3)
- ALTAIR SEMICONDUCTOR LTD (1)
- AMIMON LTD. (2)
- ARRAYCOMM INC (1)
- ATC TECHNOLOGIES LLC (2)
- AXESSTEL INC. (1)

### Information

Patent Charts
Patents
Products


Name
AT86RF525B
AT86RF535B
BCS200 Chipset
MS120 Chipset
ComMAX&acirc;□&cent; CM1100
MSC8144
WiMAX Connection 2250
NW1000 Platform
NW2000 Platform
SQN1110
SQN1130

#### WiMAX Connection 2250

Intel

**Description:**  
\* OFDM 256 PHY mode with support for channel bandwidths up to 10 MHz \* TDD and H/FDD duplexing modes \* Concatenated Reed-Solomon and Convolutional Encoding Forward Error Correction \* Adaptive modulation (BPSK, QPSK, QAM16, QAM64) \* Enhanced link budget support \* Payload Header Suppression \* IPv4, IPv6, 802.3 Convergence Sub-Layers \* ARQ, HARQ \* UGS, RT-VR, NRT-VR, ERT-VR, and BE QoS classes \* Sleep and Idle mode power management support \* 802.16 Authorization Policy and EAP Authorization Category: System on Chip (SoC) Spectrum Frequency: N/A

**Summary:**  
null



Preview of the products for particular company  
**Like this report?**

**This is only a sample report with brief analysis  
Dolcera can provide a comprehensive report customized to your needs**

Buy the customized report from Dolcera		
Patent Analytics Services	Market Research Services	Purchase Patent Dashboard
Patent Landscape Services	Dolcera Processes	Industry Focus
Patent Search Services	Patent Alerting Services	Dolcera Tools

## WiMAX

### WiMAX Dashboard

- WiMAX is defined as "Worldwide Interoperability for Microwave Access" by the WiMAX Forum, formed in June 2001 to promote conformance and interoperability of the IEEE 802.16 standard, officially known as WirelessMAN. WiMAX aims to provide wireless data over long distances, in a variety of different ways, from point to point links to full mobile cellular type access. In practical terms this enables a user, for example, to browse the Internet on a laptop computer without physically connecting the laptop to a wall jack.

### Background Information

**Spectrum coverage by geography** Image below shows the spectrum for WiMAX users World wide.



FREQUENCY	USES
2-11 GHZ	What the IEEE 802.16-2004 specifies as the operating range for point to multi-point operations
1.7 and 2.1 GHz	Advanced Wireless Services in US; potentially a spectrum of choice for AWS spectrum holders (legacy service providers)
2.3 GHz	Wireless Communications Services in US; expect incumbent service providers who already hold this spectrum to use it for WiMAX services
2.4 – 2.483 GHz	ISM and FCC Part 15, largely unlicensed, used for Wi-Fi; to be avoided by WiMAX operators on concerns of interference from Wi-Fi
2.5 GHz	BRS/EBS in US; - Projected as being a popular licensed WiMAX spectrum choice in US and for those who could not get 3.5 GHz in other nations, probably the second most popular spectrum vendors will build product for
3.5 GHz	Unlicensed in many nations outside the US. Many nations have allocated it as the WiMAX spectrum. Almost all vendors offer WiMAX product for this frequency. Not useable commercially in the US, as it is spectrum held by the military.
3.65 GHz	FCC issued an announcement in 2004 promoting opening spectrum here for quasi-unlicensed use. Has yet to be finalized. Many products made for 3.5 GHz may work well in 3.65 GHz US application
4.9 GHz	aka “Public Safety”, in the US, intended for use by First Responders (police, fire, ambulance and other emergency services)
5.4 and 5.8 GHz	US unlicensed; many vendors will offer this as their US unlicensed spectrum offering



#### Spectrum for WiMAX users World wide Market research data:

- Worldwide WiMAX equipment revenues are forecast to reach \$3.26 billion in 2009
- Worldwide outdoor wireless mesh access node sales are forecast to reach \$1.17 billion in 2009
- Samsung leads overall WiMAX equipment revenue share in 3Q06, ahead of Alvarion, Airspan, and Aperto Networks
- Strix Systems leads overall outdoor mesh revenue market share in 3Q06, just ahead of Tropos Networks and BelAir Networks
- 35% of WiMAX equipment sales come from Asia Pacific, 30% from EMEA, 20% from North America, and 14% from CALA
- 49% of wireless mesh access node sales come from North America, 25% from EMEA, 18% from Asia Pacific, and 8% from CALA
- 802.16 standards The first 802.16 standard was approved in December 2001. It delivered a standard for point to multipoint Broadband Wireless transmission in the 10-66 GHz band, with only a Line of Sight (LOS) capability. It uses a single carrier (SC) physical (PHY) standard.

Source

#### Standards

1. IEEE 802.16-2004 (802.16d) addresses only fixed systems
2. IEEE Std 802.16e-2005, also called mobile WiMAX
  - ♦ 802.16e also bring Multiple Antenna Support through Multiple-input multiple-output communications. This brings potential benefits in terms of coverage, self installation, power consumption, frequency re-use and bandwidth efficiency. 802.16e also adds a capability for full mobility support.
3. WiMAX II, 802.16m will be proposed for IMT-Advanced 4G (future development)
  - ♦ 3GPP LTE and WiMAX-m are concentrating much effort on MIMO-AAS, mobile multi-hop relay networking and related developments needed to deliver 10X and higher Co-Channel reuse multiples.


#### IEEE 802.16e-2005 improves upon IEEE 802.16-2004 by:

- Scaling of the Fast Fourier Transform (FFT) to the channel bandwidth in order to keep the carrier spacing constant across different channel bandwidths (1.25-20 MHz). Constant carrier spacing results in a higher spectrum efficiency in wide channels, and a cost reduction in narrow channels. Also known as Scalable OFDMA (SOFDMA).
- Improving NLOS coverage by utilizing advanced antenna diversity schemes, and hybrid-Automatic Retransmission Request (hARQ)
- Improving coverage by introducing Adaptive Antenna Systems (AAS) and Multiple Input Multiple Output (MIMO) technology
- Increasing system gain by use of denser sub-channelization, thereby improving indoor penetration
- Introducing high-performance coding techniques such as Turbo Coding and Low-Density Parity Check (LDPC), enhancing security and NLOS performance
- Introducing downlink sub-channelization, allowing administrators to trade coverage for capacity or vice versa



- Enhanced Fast Fourier Transform algorithm can tolerate larger delay spreads, increasing resistance to multipath interference
- Adding an extra QoS class (enhanced real-time Polling Service) more appropriate for VoIP applications.
- Adding support for mobility (soft and hard handover between base stations). This is seen as one of the most important aspects of 802.16e-2005, and is the very basis of 'Mobile WiMAX'. [Source](#)

## Technology mapping parameters



## IEEE 802.16e Protocol Stack

### Content delivery


### QoS service for WiMAX Content Delivery as per standard

	UGS	RT-VR	NRT-VR	BE	ERT-VR
Service	<b>Unsolicited Grant Service</b> Real time service (e.g.VoIP) generating fixed data rate. Data can be provided as either fixed or variable length PDU.	<b>Real-Time Variable Rate Service</b> Real-time service (e.g.MPEG) applications with variable bit rates. Require guaranteed data rate and delay.	<b>Non-Real-Time Variable Rate service</b> Non Real time service (FTP) for guaranteed data rate.This service is insensitive to delays.It is desirable in certain cases to limit the data rate of these services to some maximum rate.	<b>Best Efforts Service</b> The intent of the BE service grant scheduling type is to provide efficient service for best effort traffic in the uplink.	<b>Extended Real-Time Variable Rate Service.</b> This service is to support real-time applications with variable data-rates, which require guaranteed data and delay, for example VoIP with silence suppression.
Parameters	1) Minimum reserved traffic rate 2) Maximum Latency 3)Request/Transmission Policy 4) Unsolicited Grant Interval	1) Maximum Latency 2) Minimum Reserved Traffic Rate 3) Maximum Sustained Traffic Rate 4) Traffic priority 5)Request/Transmission policy 6) Unsolicited Polling Interval	1) Minimum Reserved Traffic Rate 2) Maximum Sustained Traffic Rate 3) Traffic priority 4)Request/Transmission policy	1) Maximum Sustained Traffic Rate 2) Traffic priority 3)Request/Transmission policy	1) Maximum Latency 2) Tolerated Jitter 3) Minimum Reserved Traffic Rate 4) Maximum Sustained Traffic Rate 5) Traffic Priority 6)Request/Transmission Policy 7) Unsolicited Grant Interval

## WiMAX Network Reference Model

**Access Service network(ASN):** The ASN coordinates traffic across multiple Base Transceiver Stations (BTS) and supports security, handoffs and Quality of Service (QoS).

- The ASN interfaces the BTS and the all-IP core network?the CSN. Typically the ASN includes numerous BTSs with one or more ASN gateways.
- The ASN manages radio resources, MS access, mobility, security and QoS. It acts as a relay for the CSN for IP address allocation and AAA functions.



**WiMAX Network Reference Model**

Interface	Description	Functionality
R1	Interface between the MS and the ASN	Air interface
R2	Interface between the MS and the CSN	AAA (Authentication, Authorization, & Accounting ), IP host configuration, mobility management
R3	Interface between the ASN and the CSN	AAA, policy enforcement, mobility management
R4	Interface between the ASNs	Mobility management
R5	Interface between the CSNs	Internetworking,roaming
R6	Interface between BTS and ASN gateways	IP tunnel management to establish and release MS connection
R8	Interface between the BTSs	Handoffs

#### ASN Gateway functions

- Service Flow Authorization
- Authentication and key distribution
- Session/Context maintenance
- Handover co-ordination & Mobility management
- Paging control
- Accounting client
- DHCP proxy/relay
- MIP client/FA
- Data-path management and (re)-anchoring
- Policy Enforcement
- Multiple BS, ASN, CSN configurations

#### Companies

- [List of companies](#)

## Products

Table below shows some of the products using WiMAX technology.

Company	Product		Image
	Main category	Sub category	
<a href="#">Intel</a>	System on Chip (SoC)	WiMAX Connection 2250	
<a href="#">Redline Communication</a>	Subscriber station	RedMAX? Indoor Subscriber Unit (SU-I)	
<a href="#">Airspan</a>	Base station	HiperMAX	
<a href="#">Samsung</a>	WiMAX mobile phone	Samsung SPH-P9000 Cellphone	
<a href="#">Navini networks</a>	Antenna system	Ripwave? MX 2.3GHz	

## Sample analysis

- [Mobile WiMAX spreadsheet](#)

## Conferences

- [WiMAX world conference - 2008 in USA.](#)
- [Big-name vendors lined up to offer WiMAX laptops](#)
- [Mobile WiMAX: The Attack Plan](#)
- [WiMAX Strategies 2007](#)
- [GSM>3G ME - The Leading Middle Eastern Communications Event - Dubai, UAE](#)
- [WiMAX 2007](#)
- [ISPCON fall - 2007](#)
- [IPTV world forum - 2007 Middle East & Africa](#)
- [Mobile Internet World conference - 2007](#)
- [Strategies for digital living markets - 2007 \(Connections - Europe \)](#)
- [IPTV Asia - 2007](#)
- [IPTV World Forum Latin America 08](#)
- [WCA International Symposium & Business Expo](#)
- [IPTV World Forum 08](#)
- [WiMAX Forum Congress Asia - 2008](#)
- [WiMAX Forum Global Congress - 2008](#)
- [WiMAX Forum Congress Americas - 2008](#)
- [WCA - 2008 Capitalizing on the 4G/WiMAX Eco-System](#)
- [The Professionals Meridian Conferences](#)
- ['Broadband & Beyond' conference highlights WiMAX technology](#)
- [Amsterdam conference addresses WiMAX trends and issues](#)
- [WiMAX ? Financial, Services, Technology Trends for Service Providers](#)
- [2007 WiMAX Forum Taipei Conference](#)
- [4th MOBILE WiMAX Forum PlugFest 4th MOBILE WiMAX Forum PlugFest](#)
- [The 1st South Asia Broadband Communications Congress & Expo](#)
- [India ? Hub for Telecom Manufacturing & Exports](#)
- [ASSOCHAM Frost & Sullivan International Conference on Broadband 2007](#)
- [CommunicAsia 2007](#)
- [WiMAX World Europe 2007](#)
- [3rd Mobile WiMAX Forum PlugFest](#)
- [15th Convergence India 2007](#)
- [2nd Mobile WiMAX Forum PlugFest](#)
- [India Telecom 2007](#)
- [WiMAX Focus](#)

## WiMAX deals

- [Intel wins Nokia mobile WiMAX deal](#)
- [Samsung, Sprint in WiMAX deal for NYC](#)
- [Clearwire, Sprint Near WiMAX Deal -- WSJ](#)
- [CTIA: Moto wins ninth WiMAX deal; launches new BTS](#)
- [UK's picoChip wins WiMAX deal with China's ICT](#)
- [Motorola has secured two contracts to build WiMAX networks in Taipei, Taiwan.](#)
- [Intel mum on WiMAX deal in central China](#)
- [Nortel, Toshiba in WiMAX deal](#)



- Sprint, Nokia Ink WiMAX Deal
- Airspan, Umniah WiMAX deal
- ZyXEL and Sprint sign deal for WiMAX customer premise equipment
- Intel Makes Largest Investment Ever in WiMAX Deal with Clearwire and Motorola
- Pipex pens WiMAX deal with Nokia Siemens Networks
- Nortel Scores WiMAX Deal in U.S.
- DoCoMo, Acca ready WiMAX deal
- AOL and Clearwire Seal WiMAX Deal
- Nera wins Africa WiMAX deal.

## WiBro

WiBro is an acronym for wireless broadband and is actually a term that is in the process of being phased out in favor of the more collaborative and generic Mobile WiMAX.

- Korean standards makers early on adopted the term to describe their initiatives towards adopting a version of the 802.16e standard.
- Basically, the Korean standard chose to accept a specific mobile WiMAX iteration of 802.16e, rather than any future version that included backwards compatibility to fixed wireless 802.16 systems.
- Korea enjoys probably the most extensive 3G deployments in the world already, and its fixed broadband access per capita is the highest in the world. What it needed was an improved mobile broadband. In fact, the Korean government issued the first three deployment licenses for WiBro/Mobile WiMAX in January of 2005.
- WiBro/Mobile WiMAX in many respects is driving the mobile side of WiMAX at least from the point of view of vendors eager to provide products to these early deployments. This decision however, results in a backwards compatibility problem with Fixed WiMAX standards or 802.16-2004.
- The smooth interoperability of previous WiBro gear from Samsung with other vendors such as Motorola should be cemented this year as these two companies along with Intel have been chosen as the primary vendor for Sprint Nextel's WiMAX deployment. The two companies clearly have a powerful incentive for their products to work seamlessly.

## Standards

- WiBro is an integral part of IEEE 802.16e


## Companies






- [List of companies supporting WiBro technology](#)


## Industry news:

- South Korean telco SK Telecom and Wavesat, a Canadian developer of a WiMAX chipset, software and development platform have signed an agreement to cooperate in the development of WiBro/OFDMA technology for next generation mobile devices.
- Wavesat will work with SK Telecom (SKT) to develop WiBro/OFDMA systems-on-chips (SoCs), system tools and a development kit based on the WiBro 802.16e S-OFDMA profile. The U-mobile product portfolio from Wavesat will allow WiMAX wireless system providers (OEMs/ODMs) worldwide to develop and deploy fully mobile WiMAX and WiBro solutions. [Source](#)

## Products Overview

Company	Product		Image
	Main category	Sub category	
	Mobile Station	<a href="#">M8000 WiBro handset</a>	

		<a href="#"><u>Super WiBro Phone</u></a>	
		<a href="#"><u>WiBro-enabled notebook pc</u></a>	
	Access control Router	<a href="#"><u>Access control Router</u></a>	
Kisan Telecom	Base station	<a href="#"><u>WiBro Repeater</u></a>	
i-River	Mobile Station	<a href="#"><u>G10 games console</u></a>	

Korea Telekom	USB modem	<a href="#">iPlug Premium</a>	
---------------	-----------	-------------------------------	--


## 3GPP Long Term Evolution

3GPP LTE (Long Term Evolution) is the name given to a project within the Third Generation Partnership Project to improve the UMTS mobile phone standard to cope with future requirements.

- LTE focus is on Enhancement of the Universal Terrestrial Radio Access (UTRA) and Optimisation of the UTRAN architecture.
- Downlink based on OFDMA (OFDMA offers improved spectral efficiency, capacity, etc)
- Uplink based on SC-FDMA (single carrier) (SC-FDMA is technically similar to OFDMA but is better suited for uplink from hand-held devices- more considerations on battery power)

## Standards


- Download rates of 100 Mbit/s, and upload rates of 50 Mbit/s for every 20 MHz of spectrum
- At least 200 active users in every 5 MHz cell. (ie 200 active phone calls)
- Sub-5ms latency for small IP packets
- Increased spectrum flexibility, with spectrum slices as small as 1.25 MHz (and as large as 20 MHz) supported (W-CDMA requires 5 MHz slices, leading to some problems with roll-outs of the technology in countries where 5 MHz is a commonly allocated amount of spectrum, and is frequently already in use with legacy standards such as 2G GSM and cdmaOne.) Limiting sizes to 5 MHz also limited the amount of bandwidth per handset
- Optimal cell size of 5 km, 30 km sizes with reasonable performance, and up to 100 km cell sizes supported with acceptable performance
- Co-existence with legacy standards (users can transparently start a call or transfer of data in an area using an LTE standard, and, should coverage be unavailable, continue the operation without any action on their part using GSM/GPRS or W-CDMA-based UMTS)







## 3GPP LTE protocol stack Companies

- [List of companies supporting 3GPP technology](#)

## Products

Company	Products		Image
	Main category	Sub category	
<a href="#">Rohde &amp; Schwarz</a>	Signal Analyzer	FSQ Signal Analyzer	

<a href="#">Pourseyed UBC IEEE PDF.pdf Sierra Wireless</a>	PC cards	PC card	
<a href="#">Anritsu Company</a>	Test Systems	MX785201A test systems	
<a href="#">Anritsu Company</a>		MD8480C signaling tester	
<a href="#">Picochip</a>	Bse station	Base station damo	

## HSOPA

High Speed OFDM Packet Access (HSOPA) is a proposed part of 3GPP's Long Term Evolution (LTE) upgrade path for UMTS systems. HSOPA is also often referred to as Super 3G. If adopted, HSOPA succeeds HSDPA and HSUPA technologies specified in 3GPP releases 5 and 6. Unlike HSDPA or HSUPA, HSOPA is an entirely new air interface system, unrelated to and incompatible with W-CDMA. Features of HSOPA

### Standards

- Flexible bandwidth usage with 1.25 MHz to 20 MHz bandwidths. By comparison, W-CDMA uses fixed size 5 MHz chunks of spectrum.
- Increased spectral efficiency at 2-4 times more than in 3GPP release 6, peak transfer rates of 100 Mbit/s for downlink and 50 Mbit/s for uplink.
- Latency times of around 20 ms for round trip time from user terminal to RAN, approximately the same as a combined HSDPA/HSUPA system, but much better than "classic" W-CDMA.

### Design

HSOPA uses Orthogonal Frequency Division Multiplexing (OFDM) and multiple-input multiple-output (MIMO) antenna technology to support up to 10 times as many users as W-CDMA based systems, with lower processing power required on each handset.[1]. Still in development, experimental performance is 37 Mbit/s in the downlink over a 5 MHz channel, close to the theoretical maximum of 40 Mbit/s.

### Companies

- [List of companies supporting HSOPA technology](#)

### Products

Company	Products		Image
	Main category	Sub category	
<a href="#">Orange</a>	PC crad	PC card	



			
<a href="#">Samsung</a>	Mobile	SGH-Z620	
<a href="#">T - mobile</a>		MDA Vario III	
<a href="#">Sarian</a>	Router	HR4110 HSDPA router	
<a href="#">Centro technologies</a>	RF HSDPA Test Cases	MINT T1152-HSDPA	

## 3GPP2 Ultra Mobile Broadband

UMB (Ultra Mobile Broadband) is the brand name for the project within 3GPP2 to improve the CDMA2000 mobile phone standard for next generation applications and requirements. The system employs OFDMA technology along with advanced antenna techniques to provide peak rates of up to 280 Mbit/s.

Goals for UMB:

- Improving system capacity
- Greatly increasing user data rates throughout the cell
- Lowering costs
- Enhancing existing services
- Making possible new applications, and
- Making use of new spectrum opportunities.

The technology will provide users with concurrent IP-based services in a full mobility environment. The UMB standardization is expected to be completed in mid 2007, with commercialization taking place around mid-2009.

### Standards

- OFDMA-based air interface
- Frequency Division Duplex
- Scalable bandwidth between 1.25-20 MHz (OFDMA systems are especially well suited for wider bandwidths larger than 5 MHz)
- Supports mixed cell sizes, e.g., macro-cellular, micro-cellular & pico-cellular.
- IP network architecture
- Supports flat, centralized and mixed topologies
- Data speeds over 275 Mbit/s downstream and over 75 Mbit/s upstream [Source](#)

[More information](#)

### Key features



- Multiple radio and advanced antenna techniques
  1. Sophisticated control and signaling mechanisms (minimized) combine the best aspects of CDMA, TDM, OFDM, and OFDMA into a single air interface
  2. Multiple Input Multiple Output (MIMO) and Space Division Multiple Access (SDMA)
  3. Improved interference management techniques
- Ultra-high mobile broadband peak data rates
  1. Up to 280Mbps peak data rate on forward link
  2. Up to 68Mbps peak data rate on reverse link
- Ultra-low network latency
  1. An average of 16.8 msec (32-byte, RTT) end-to-end network latency
- Enhanced VoIP capacity and user experience
  1. Up to 500 simultaneous VoIP users (10 MHz FDD allocations)
- Scalable IP-based flat or hierarchical architecture
  1. Greater service deployment flexibility, improved performance, and lower cost of ownership
- Flexible spectrum allocations
  1. Scalable, non-contiguous and dynamic channel (bandwidth) allocations
  2. Support for bandwidth allocations of 1.25 MHz, 5 MHz, 10 MHz and 20 MHz
- Less power consumption
  1. Improved battery life


[Source](#)

### Companies


- [List of companies supporting 3GPP2 UMB technology](#)

### Products

Company	Products		Image
	Main category	Sub category	
<a href="#">OQO Inc</a>	Ultra mobile PC	OQO Model 2 ultra mobile	
<a href="#">3 Mobile</a>	Broad band USB	Mobile Broadband USB modem	

<a href="#">Sprint</a>	Mobile Broadband Card	EV-DO card	
<a href="#">Qualcomm</a>	Base station	Base station	N/A

## Process Chart



## Like this report?

This is only a sample report with brief analysis  
Dolcera can provide a comprehensive report customized to your needs

Buy the customized report from Dolcera		
<a href="#">Patent Analytics Services</a>	<a href="#">Market Research Services</a>	<a href="#">Purchase Patent Dashboard</a>
<a href="#">Patent Landscape Services</a>	<a href="#">Dolcera Processes</a>	<a href="#">Industry Focus</a>
<a href="#">Patent Search Services</a>	<a href="#">Patent Alerting Services</a>	<a href="#">Dolcera Tools</a>

## Contact Dolcera

**Samir Raiyani**

**Email:** [info@dolcera.com](mailto:info@dolcera.com)

**Phone:** +1-650-269-7952